

# Foam Cleaning Equipment Injector LP 1,5-5

Low Pressure

Item no.: 88020



1,5-5 Bar

## Purpose and use.

The Injector LP 1,5-5 is wall mounted, compact and designed for easy use and service. It is for sites that require cleaning by Foaming and Disinfection.

It is capable of producing a dry dense foam and by adjusting the air pressure, a more wet dense foam.

The Injector LP 1,5-5 is manual operated by valves, which is easy to operate. All materials that is in contact with the product, is corrosion resistant.

## Features / benefits.

Functions:	Cleaning with Foam / Disinfection
Operator friendly:	Easy understanding of the functions
Variable foam density:	Capable of producing dry dense foam Capable of producing wet dense foam
Adjusting product conc.:	Easy change of concentration by changing the colour coded orifice nozzle
Few installation requirements:	No electricity required



## General Description

The Injector works like a hydraulic foam cabinet, (the Injector is essentially a “static pump”). Injectors work on the principle of a pressure differential: A vacuum is created which pulls “or pumps” the product into the mixing chamber. As standard, a non return valve is mounted in the water inlet.

## Ordering Information

Shipping: All correspondence concerning shipping, should be directed to: Mrs. Lene Wittendorf

## Placing Orders and Enquiries:

All orders will be acknowledged by fax, unless other special arrangements have been made.

All correspondence concerning new orders or progressing existing orders, should be directed to:

Mr. Anders S. Christensen  
order@scanfoam.com

## Technical enquiries:

Enquiries relating to product performance should be directed to:

Mr. Aksel A. Utoft  
Mr. Anders S. Christensen

**ScanFoam®** Cleaning Equipment ApS.  
Niels Bohrs Vej 29b, Stilling  
8660 Skanderborg  
Denmark

Telephone: +45 86 57 25 99  
Fax.: +45 86 57 20 86  
E-mail: anders.christensen@scanfoam.com  
order@scanfoam.com

## Specifications

Water inlet:	Connection:	1/2" BSP (Female)
Limitation:	Min. feed pressure	1,5 bar
	Max. feed pressure	5 bar
	Max. temperature	50 °C

Water consumption at 5 bar & 10 m 3/4" hose:	
Foaming	5 l/min

Air inlet:	Connection	1/4" BSP Female
Limitation:	Min. feed pressure	3 bar
	Max. feed pressure	5 bar
Air consumption at 5 bar		180 l/min

Prod. inlet:	Connection:	1 suction tube.
	Dosing range	1-6%

Outlet:		
Hose included 3/4" special		10 meter
Other length on request		

Weight:		6 kg
---------	--	------

